



PLANT: 3565 N HAZEL FRESNO, CA 93722
 MAIL: 4460 W. SHAW # 262 FRESNO, CA 93722
 TEL 559 441-7703 FAX 559 441-7741
 E-MAIL: gregorboat @ cs.com
 WEBSITE: gregorboats.com

THE SPORTSMAN 16&18 Walk-Thru



SPORTSMAN 16 WT SHOWN W/OPTIONAL CONTROLS

The Sportsman Walk-Thru Series is for the discriminating, serious fisherman on a budget who desires quality, durability and seaworthiness in a simple, basic walk through windshield boat.

The **Sportsman Walk-Thru** has the same design and engineering features found in the Eagle Series boats. Features such as: Welded Coaming, Deep-V Longitudinal Stringer/Transverse Bulkhead Structural System w/ Injected Foam, plus welded-in windshield, aluminum hatches, and welded-on cleats. Efficiency? Gregor has no equal. You don't need large horsepower required of boats with less demanding design and production standards. Durability? Our engineered Longitudinal Stringer / Transverse Bulkhead System coupled with Injected Foam translate into superior structural integrity and durability, plus sound deadening for a quieter ride.

STANDARD FEATURES

- ◆ Level Shear ◆ One Piece Bottom ◆ Unitized Construction ◆ 5052 & 6063 Marine Aluminum Alloy ◆ Heavy Duty Extruded Double-Wall Box Chine
- ◆ Enhanced Longitudinal/Transverse Bulkhead Integrated Structural System ◆ Welded Coaming ◆ Extra Large Bow Plate ◆ Welded -in Windshield
- ◆ Full Length Pressed-in Splash Rail ◆ Bow Eye, Welded On ◆ Stern Eyes, Welded on ◆ Bow Platform w/ Compartment with Aluminum Cover
- ◆ Self Bailing Motorwell ◆ Injected Foam Level Floatation ◆ Full Length Flat Floorboards ◆ Deluxe Upholstered Seating ◆ Under Seat Storage ◆ Bilge Pump
- ◆ Navigation Lights ◆ Glove Box

OPTIONAL FEATURES

- ◆ Bow Rails – Welded On ◆ Side Rails –Welded On ◆ Stern Down Rigger Brackets – Welded On ◆ ◆ Live Well in Bow ◆ Tilt Steering • SS Steering Wheel
- ◆ Aluminum Storage Boxes w/ Deluxe Upholstered Seating ◆ Premium Seating Upgrade ◆ Instrument Panel w/ Tach, Voltmeter, Fuel Gage & Fused Switches
- ◆ 12 V. Accessory Plug ◆ Pre-rigged Engine Controls

SPECIFICATIONS-

LENGTH	BEAM	DEPTH			TRANS HT	HULL WT	HULL THICKNESS	MAX CAP				
		BOW	AMID	STERN				LBS	PER	HP		
16	84 "	31"	30"	26"	20"	675 lbs	Longitudinal Stringer/ Transverse Bulkhead Integrated Structural System w/ .080 Bottom & Sides & Injected Foam			1125	5	50
18'	84 "	31"	30"	26"	20"	750 lbs				1180	5	60

SPECIFICATIONS AND FEATURES SUBJECT TO CHANGE WITH OUT NOTICE.

